AquaBay M4 -HDD Waterblock

P/N : CL-W0082 **Application 5.25" drive bay**

O4329D

Limited Liability

These warranties replace all other warranties, expressed or implied including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. Thermaltake disclaims all other warranties, expressed or implied including, without limitation, implied warranties of merchantability and fitness for a particular purpose. Some jurisdictions do not allow the exclusion of implied warranties so this limitation may not apply to you. All expressed and implied warranties are limited in duration to the limited warranty period. No warranties apply after that period, some jurisdiction do not allow limitation on how long an implied warranty lasts, so this limitation may not apply to you.

Limitations of liability, Thermaltake's responsibility under this, or any other warranty, implied or expressed, are limited to repair or replacement, as set forth above. These remedies are the sole and exclusive remedies for any breach of warranty. Thermaltake is not responsible for direct, special, incidental, or consequential damages resulting from any breach of warranty or under any other legal theory including, but not limited to, lost profits, downtime, goodwill, damage to or replacement of equipment and property, and any cost of recovering, reprogramming, or reproducing any program or data stored in or used with a system containing Thermaltake product. Some jurisdictions do not allow the exclusion or limitation of incidental or exclusions may not apply to you.

Extent of limited warranty, Thermaltake does not warrant that your product will be free from design defects or errors known as " ERRATA". Current characterized errata are available upon request. This limited warranty does not cover any costs relating to removal or replacement of any part that is soldered or otherwise affixed to your system's motherboard. This limited warranty does not cover damages due to external causes, including accidental, problems with electrical power, usage not in accordance with product instructions, misuse, neglect, alteration, repair, improper installation, or improper testing. Nor is Thermaltake held liable for any bodily damage that may result during the installation, maintenance, repair, or is otherwise associated with this product, Thermaltake is free from any legal actions that may result in death, pain and anguish, or any other form of personal damage that may occur by purchasing this product.

You, the buyer, agree to this warranty and its term set within its expressed and implied limited warranty. This limited warranty gives you specific legal rights, and you may also have other right that varies from jurisdiction to jurisdiction.

Components checking >>

A. The main body of HDD Waterblock
B. Quick install connectors
(ID 6.4mm x 2 / ID 9.5mm x 2)
C. Gaskets x 2(90x70x2mm)
D. Tubes x 2
(ID 6.4mm UV tube x 150cm)
(ID 9.5 mm UV tube x 200 cm)
E. Screws x 8

A.

B.

C.

D.

E.

Thermaltake
COOLall YOUR LIFE

AquaBay M4 -HDD Waterblock

2.

P/N : CL-W0082 **Application 5.25" drive bay**

Installation

O4329D

A.Install the HDD Waterblock into your chassis >>

Tear off the paster of the first gasket and cut off a half circle from it to ensure the bearing of HDD will not be blocked by this gasket.

>

Attach the first gasket to the HDD and take the half circle gasket to paste it on the bearing as shown in photo.

>

Take the second gasket and tear off the paster. Attach it on top of the first gasket as shown in photo.

>

Recommendation: You need to check the dimension of HDD to ensure how many gaskets to be installed.

Secure the HDD and aluminum cover together by tightening 4 screws on top of aluminum cover.

>

Select the quick install connectors (ID6.4 mm or ID 9.5 mm) that fit your system.

>

Screw the connectors to the liquid inlet and outlet as shown in photo.

>

Caution: Choose the quick install connectors and UV tubes (ID 6.4 mm or 9.5 mm) that fit your liquid cooling system.

Take apart the nut and insert UV tube to the screw of quick install connector on liquid inlet. Do the same action to the liquid outlet.

>

Installation complete.

>

Remove the front panel. Insert the HDD waterblock into the drive bay space.

>

Secure the HDD waterblock with screws or clip.

Thermaltake
COOLall YOUR LIFE

www.thermaltake.com 2005.11

AquaBay M4 -HDD Waterblock

P/N : CL-W0082 Application 5.25" drive bay

Installation

O4329D

B. Upgrade your BigWater SE with VGA waterblock(Apply to the liquid cooling system for ID 6.4mm tubes and connectors) >>

Figure A

Figure B

Take apart the quick install connector on outlet of pump. Use a container to keep the liquid flow out from the tube.

>

Repeat the same action to take apart inlet of the pump.

>

Caution: Make sure all liquid has been removed before proceed to the next step.

AquaBay M4 -HDD Waterblock

P/N : CL-W0082 Application 5.25" drive bay

Installation

Reinstall the quick install connectors and tubes back to the pump.

>

Take apart the quick install connector on outlet of VGA waterblock.

>

Remove the UV tube connecting from outlet of VGA waterblock to inlet of radiator.

>

Take the UV tube from inlet of HDD Waterblock and use quick install connector to connect to outlet of VGA waterblock.

>

Take the UV tube from outlet of HDD Waterblock and use the quick install connector to connect to inlet of radiator.

>

Upgrade Installation complete.

>

Replace the front panel of chassis to complete the installation. Refill liquid after completing the installation

Recommendation: Please fill the coolant according to the manul of Big Water SE.

Note :

O4329D